



Product Specification Sheet

Roplay VARIO S

Product name	Roplay VARIO S
Item number	7030012300000
Recommended age group	3+
Falling Height (EN 1176)	1,65 m (5'-5")
Length, width, height	3,0 x 2,9 x 2,5 m (9'-10" x 9'-6" x 8'-2")
Protective Surfacing Area required (EN 1176)	6,2 x 6,2 m (20'-4" x 20'-4")
Minimum space required (EN 1176)	30,1 m ² (324 ft ²)
Ground anchor plates 700 mm below level	5
Number of skilled installers needed	2
Installation time without foundation	3 hours
Dimensions of largest part	Ø 0,05 x 1,47 m (Ø 1 7/8" x 4'-10")
Weight for heaviest part	40 kg (88 lbs)
Freight volume	1,3 m ³ (46 ft ³)
Gross weight	200 kg (441 lbs)
Spare part guarantee	Lifelong
Certificate No. EN 1176	Z1A 14 03 10256 204



Product description:

Roplay VARIO S, icosahedron space framework, Height 2,5 m (8'-2") with a single Bucky-Ball net structure.

All anchor points are equipped with a central single-point tensioning system warranting that no fastening element or rope eyelet is accessible to users. The 25 steel members Ø 48,3 x 1466 mm (Ø 1 7/8" x 4'-10") in the framework are corrosion resistant and powder-coated environmentally sound.

The 11 aluminum-cast nodes in the framework are also coated in the zinc-powder-process.

The spatial netting is made of polyester-coated steel cables (U-Rope®) with a diameter of 16 mm (5/8"). Contrary to cable coatings out of polypropylene the polyester is more abrasion-resistant and color fast to UV-light. The steel wires are drawn galvanized.

As cross connectors in the spatial netting aluminium-cloverleaf rings are being used that have been proven in 20 years of employment.